MODEL 72 - 2600



Calender used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting heatsetting

1. Characteristics of printing cylinder:

1.1. Diameter: 200 mm (7,87"). 1.2. Width: 2.600 mm (102,36")...

1.3. Working width: 2.200 mm (86,61") / 2.400 mm (94,49")...

2. Heating system and temperature control:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. Tension controls

- 3.1. Tension control for material:
 - Entry: mechanic brake with manual adjustment and fabric manual brake
 - Exit: tangential winding on felt
- 3.2. Tension control for printing paper:
 - Entry: disk brake with pneumatic adjustment.
 - Exit: winding motor with pneumatic device
- 3.3. Tension control for protection paper:
 - Entry: disk brake with automatic adjustment.
 - Exit: tangential winding on felt

4. Other devices into machine

- 4.1. NOMEX felt with tension adjustment system and automatic felt-centering device
- 4.2. Incorporated system of felt protection in case of black out and/or compressed air lack

5. Technical data

5.1. Installed power: 16 kw/h

5.2. Average electric consumption: 11 kw/h

5.3. Compressed air pressure: 6-8 bar

5.4. Mechanic speed: 0.1 - 1.7 m/min

All data and technical features are purely indicative and subjected to changes without prior notice.











STANDARD & CUSTOM HEATING SOLUTIONS





MODEL 72 - 2600



5.6. Net weight: 2.390 kg

5.7. Machine produced according to EC rules

5.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice.







STANDARD & CUSTOM HEATING SOLUTIONS



