

## MODEL 858



Special calender for pieces or continuous fabrics, used for :

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

### 1. Characteristics of printing cylinder:

1.1. Diameter : 800 mm (31,49").

1.2. Width : 2.200 mm (86,61").

1.3. Working Width: 1.800 mm (70,87") / 2.000 mm (78,74").

### 2. Heating system and temperature control:

2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.

2.2. The temperature of the cylinder is set by a touch screen and regulated directly through an electronic sheet. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

### 3. Tension controls:

3.1. Tension control for printing material in roll:

- Entry: disk brake with manual adjustment + fabric manual brake
- Exit: independent motorization with control by potentiometer

3.2. Tension control for printing paper in roll:

- Entry: disk brake with pneumatic adjustment
- Exit: independent motorization with control by potentiometer

3.3. Tension control for protection paper:

- Entry: disk brake with pneumatic adjustment
- Exit: independent motorization with control by potentiometer

### 4. Other devices into machine

4.1. Short front working table, 1500 mm

4.2. Conveyor-belt for automatic unloading on the back of the machine

4.3. Independent motors with a electronic synchronization system

4.4. NOMEX felt with tension adjustment system and automatic felt-centering device

All data and technical features are purely indicative and subjected to changes without prior notice.



## MODEL 858



- 4.5. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.6. Machine general management, including temperature controls, controlled by a programmable PLC for the production data memorization
- 4.7. Front touch-screen keyboard for several access to many work programs.

### 5. Technical data

- 5.1. Installed power: 60,5 kw
- 5.2. Average electric consumption: 39,5 km/h
- 5.3. Compressed air pressure: 6-8 bar
- 5.4. Mechanic speed: 1 – 15 m/min
- 5.5. Overall dimensions (with front table): width 3.610 mm (142"). length 4.475 mm (176"). height 2.315 mm (91").
- 5.6. Net weight (without front table): 5950 kg
- 5.7. Machine produced according to EC rules
- 5.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice.

Monti Antonio S.p.A.  
Via dell'Elettronica n°5  
36016 Thiene (VI) - Italy

Tel. +39 0445 364619  
Fax. +39 0445 364033  
sales@montiantonio.com  
[www.montiantonio.com](http://www.montiantonio.com)

STANDARD & CUSTOM HEATING SOLUTIONS



LAMINATING



PRINTING



FINISHING



PRESSING



STEAM GENERATORS